DEVELOPMENT AND COMPARISON OF SPECTROGRAPHIC METHODS FOR DETERMINATION OF ZING IN FLANT MATERIAL; SURVEY OF THE ZING CONTENT OF KANSAS GROWN ALPALPA

by

JUSTIN EUGENE HAWLEY

B. S., Kanses State College of Agriculture and Applied Science, 1947

A THESTS

submitted in pertial fulfillment of the requirements for the degree

MASTER OF SCIENCE

Department of Chemistry

KANSAS STATE COLLEGE OF ACRICULTURE AND APPLIED SCIENCE

RESULTS OF THE ALFALFA	SURVEY		3
CONCLUSIONS			,
ACKNOWLEDGRANTS		46	,
LITERATURE CITED		47	,

INTRODUCTION

There are known to exist in the earth's cruet, over 90 closests. The literature shows that sixty of these elements have been positively identified in plants (33). The amjority of these ere present, however, only in minute quantities. These classate ere known as minor elements or trees elements.

The minor elements have been divided roughly into two classes, the essential and nonsesential elements. There is, at the present time, considerable disagreement es to which elements should be placed in each division, but the following are generally recognized as essentials nine, iron, boron, manganese, and copper. As the result of extended etudy, the effect of this group of elements on plant growth is rescondibly well established. The elements such as lead, titenium, barium, and etrontium fell into the nonsesential group. Their effect on plant growth remains, so yet, to be determined.

A thorough study of the functions of minor elements in plant growth and metabolism is comparatively recent. Previous to 1932, the work with sine consisted of more or less emperical experiments. With the development of securete methods of enalysis for micro quantities, the interest pertaining to minor elements in plant metabolism has increased greatly. Indicative of this interest is the element sine. Literature shows over 250 papers dealing with mino deficiencies in the United States closs (4). This number is mounting rapidly se methods of enalysis for eine become more thoroughly established,

Enowledge that mine is essential in plant growth is not new, Earliest eccumts indicate that nine was first postulated to be essential for the growth of a fungua Asparcillus niner, in 1869 (7). Javillier (19) through his work with yeast, found increased scitrity and consumption of sugar solution by the yeast in the presence of mine. Hase (23, 24) working at the same time, datermined, by water culture methods, that mine was measurery for the growth of corn, though his work, like that of Javillier, was not well scoapted. Not until the work of Sommar and Lyman (38) and Sommer (39) was mine widely eccepted as an essential plant nutrient.

Zine deficiencies are a world-wide occurrence. The United States and 20 South and Central American countries, Europe, and the Far East have reported aims deficiencies (6). Among the pleate most commonly affected are citrus (41), pinespikes (22), peosns (1), deciduous fruits (42), and corn (3). Zine, however, has also been shown to be assential in the growth of cets (26), wheat (27), barley (39), soybeans (10), green beens (15), and others. There remain many crops which have not had their mine requirements astablished.

The symptoms of mind deficiency usually involve some form of chlorosis. Citrus, deciduous, and other tress deficient in mine cherecteristically show mottled leaf, little leaf or rosetts, or bronning. These symptoms are generally associated with some form of chlorosis. The symptoms of mine deficiency may be summarised as follows: some form of leaf chlorosis, reduced leaf cite, mmirrormetion, sount follows, and reduced fruit production

(8).

Zinc salts first came into commercial use as a fertilizar in 1932, Since that time the use of these calts as plant nutriente has grown widely. Chlorosis or yellowing of the corn plant, usually called units bod, oppears within a week or two after the seedlings energy from the ground. This condition may be controlled and overcome by the eddition of relatively small quantities of size sulfets placed in the rows before planting (3). Zinc oppears (2) and zinc dust (29) have been shown to be affective in controlling diseases of citrus trees.

The exact function of each almor element in the plant is not known singularly. The following are some of the postulated functions of minor metabolic activities, estalysis, change pH of soil through chemical reaction, detarnine ordetion states of other elements present, liberets other elements lower in electromotive series, build resistance in the plant to disease or parasites, and stimulate an effect comparable to the effect of vitamina on snimels (A5). Zinc deficiencies ere accompanied by chlorosis, and lacking contrary evidence, it may be justificily postulated that zinc is related to the formation of chlorophyll (8).

There ere no reported sine deficiencies in Ennese, and it is believed that there have been no surveys of any Kanses grown crop to determine its zine content. For this resear it essend edvisable to make such a survey. Alfairs was chosen as the crop on which to make this curvey because of the increasingly important role it is playing in the development of the etate. With increased dehydration of the crop, dehydrated alfairs has become

an important source of protein and vitamins and is used so feed for livestock and poultry. Since the boron, sodium, iron, copper, manganese, potassium, phosphorus, and calcium content of Tanase groun affaire is already known, it was fait that a curvey of the mino content of the same samples would represent a veluable sodition to the date elready swellable. The samples used for the mino survey were the same as those used for the boron curvey previously made by Smith, Schrenk, and Ting (37).

SURVEY OF THE LITERATURE

The enalysis for sine in the minute quantities in which it occurs in plant meterial is at best s very difficult one. Any analysis to be satisfactory must be sensitive to very small amounts of sine, and in addition must be sensitive to earll concentration changes. Several methods of snalysis have been proposed, but those gaining the most favor are colorimetric and spectrographic.

Hitbord (17) devised a micro method for the determination of mino using hydrogen sulfids in a solution of carefully controlled pH. This method was subject to interference by other elements precipitated by the hydrogen sulfide. Vannelow and Laurence (43) described a spectrographic procedure using the mino line at 3345.0 Angetroms, with a preliminary concentration of the mine by hydrogen sulfide. Cedadium, which was used as an internal standard, was precipitated with the mine. Research has shown that preliminary concentration of the mine is necessary if the line at 3345.0 Angetroms is to be used. Soott and Mitchell

(35) described a similar spectrographic technique, but used 8-hydroxyouincline (oxime) as a means of concentrating the mine.

Rogers (31) resommented the use of the size line at 2138.5 Angstrons which does not require a preliminary chemical concentration. Specially sensitized plates are necessary if this line is to be used. Rogers and Gall (32), compared the use of the 2138.5 Angstron line without concentration, and with chemical mathica of concentration followed by spectrographic analysis using the 3345.0 Angstron line. They gave an unfavorable report on the latter procedure. They also reported that the 2136.5 Angstron line is 30 to 50 times as sensitive as the 3345.0 Angstron line is 70 toner (28) has reported on a modified procedure similar to that of Rogers, which he has applied successfully to mixed fartilisers.

Increasing consideration has been given to adsorptionstric determination of mino, the nest presisting results being obtained from the use of diphenylthicerbeans (dithizons) as a color developing opent. Sandell (34) has employed a colorimetric dithinons method based on the work of Fischer and Leopoldi (11) for the determination of mine in soils. The dithinons gives a red to purple color when added to a solution of mine, elthough copper, lead and cobait present in the solution will interfere. The solor developed has an absorption maximum at 525 m.w. It is possible through control of pH to separate out the interfering elements as copper, lead and cobait (16). Coming and Miller (9) have suggested a "mixed color" reaction which involves the use of sodium distriplishing corbanate (cerbeants) in addition to

dithinance to get as an inhibitor to the metals previously sontioned. This modification, however, has the disadvantage that the carbanate limits the complets extraction of the sine. This objection may be overcome by caraful control of pH, volume of carbanate added, and volume of the equeous phase. This method has been adopted as a tentative method of enelysis for nine by the hasociation of official Agricultural Chemists (9).

Reed and Cumnings (30) have described a polarographic determination of sine in the presence of all the constituents ordinarily present in plant sch except those removed from the sch extract at a gli between four and five. Merrit (25) has suggested the use of 6-hydroxyquinolinate as a reagent to develop fluorescence with small quantities of sine. Beamoin has also bean suggested by White and Beamtedt (44) as a qualitative fluorescent reasons for sine.

Work in this laboratory has shown the hydrogen sulfide concentration of zino suggested by Vanselow and Leurence (A3) to be inconsistent and tedicus. Since Eogere and Cell (32) have found this mathod unfavorable too, it seemed sdviselle to investigate the concentration procedure of Scott and Mitchell (35). This investigation has led to a modification of the spectrographic technique of Scott and Mitchell (35) which give results with good eccuracy, precision, and values which compare favorably with those obtained with the dithinose colorimatric technique.

Description of Apparatus

The spectrogreph used in this recession were a bausch and Lomb large Littrow instrument with interchangeable quarks and glace option. The quarks option were used for this recession. This instrument has a wave length range of 2100 to 8000 Angetrom units and a linear dispersion of 1,5 Angetrom units per millimeters at a wave length of 3150 Angetrom units per millimeters at a wave length of 3350 Angetrom units. The quarks prism is of the Littrom type, 57 millimeters high with a reflection costing of evaporated aluminum. The combination collimating and focusing lane has a focal length of 1827 millimeters and is provided with two etops for reducing aperture.

The illuminating eystem consisted of the electrode holders, a spherical condensing lens, and a rotary sector disk. Line densities were obtained by means of an Allied Research Laboratorice-Dictort densitrometer.

The eamples were expited with a direct current generator capable of producing a potential of 150 wolks, the current depending on the recistance of the circuit. A ballect resistor was placed in cerise with the generator to stabilize the current. The sine spectrum has two lines which are considered especially suitable for quantitative analysis. They are located at 2138.6 Angstrone and 3345.0 Angstrone. The first of these two lines is sufficiently sensitive to parata analysis of the plant sah without chemical treatment. The second is, however, less censitive and the sine occurring in plant material must be concentrated by some chemical means pravious to spectrographic analysis. Table 1 shows a list of the possible interfering lines and their wave lengths (6).

Table 1. Possible interfering lines that appear in the region of the zine lines located at 2138.6 and 3345.0 Anastrons.

Element	l Line : 1 Angstroms :	Rslative line
Zine	2138.56	800R
Copper	2138.5	25
Iron	2138.589	8
Zine	3345.0	800
Chromium	3345.2	15
Molybdenum	3344.7	50
Cerium	3344.6	50

Rogere (31) and C*Concor (28) have shown that the copper end Iron lines do not interfere if they are present in concentrations not exceeding one and three percent respectively. Although chromium, molydeams, and cerium are listed as having possible interfering lines in the region of the mine line at 3345.0 Angatroms, no difficulty is experienced for two reasons: firet, the interfering elements are not present in cufficient quantity to give visible spectral lines in this region; and eccound, the dispersion of the instrument in this region is surficient that they would be resolved.

Celibration Curve for Position Five

Since the spectrum length of the large Littrow epectrograph is about 80 centimeters, it is possible to photograph only a limited portion of it at a time. There are 10 different positions of the plate and prism messessary to photograph the entire spectrum length. Position 10 was selected to photograph the mine line at 2138,6 Augstroms and position five for the mine line at 3345,0 Augstroms.

Becouse the instrument may not be in the came edjustment co when it left the featory, and the focus and tilt precerbed by the manufacturer may not be the best for the region of the opertrum in which the mine line occure, it was thought advisshle to check the recommended values of focus and tilt. This was done by photographing a caries of iron spectre with the tilt set at the recommended value and varying the focus e few divisions on each side of the given value. Emmination of the plate efter development showed the focus to be best at 108,5 for position five. Meking a similar plate setting the focus at 108,5 and verying the tilt, the tilt was found to be best at 241. These settings were used for all analyses in position five. Similar plates were made in position 10 and the best focus and tilt were found to be 218 and 136, respectively.

Because the dispersion of a prism is not linear, it was necessary to prepare a calibration curve for each position. To do this a millimeter scale was printed scrose the top of the plats and directly below this an iron spectrum. After development of the plate, the wave lengths of several iron lines were determined by comparison with a standard iron epoctrum provided with the instrument by the manufacturer. After location of a few wave lengths in this manner, others were determined using the iron spectrum charts compiled by Brode (6). The wave lengths thus determined were plotted spinst the scale reedings to obtain the dispersion curve, Fig. 1.

Selection of Internal Standard

Owniesh and Schweitzer (14) were the first to report the use of an internal standard to compensate for variations likely to occur in the ere during the axcitation of the eample. The internal standard may be one of the following two types: e weak line of e major constituent of the semple; of a small,




FIG.I. DISPERSION CURVE.

unverying amount of an element edded to each mample. Properation of a series of standard samples with varying amounts of mine and a constant amount of a reference element, followed by observation of the intensity ratio between the reference element and the sine lines, provides the basic of a working ourse.

The internal standard method essumes that varietions in excitation conditions will effect the unknown and reference element in the same manner. Also, the difference in densities of the two lines is assumed to be proportional to the logarithm of the ratio of the intensities of these lines in the source. The letter is true only for the streight line portion of the charactrictic curve of the photographic emulsion in question.

In making a series of exposures for the same sample the line densities vary widely. This is especially true of an element such as sine which is highly volatile. The principal reason for this lies in the feet that it is impossible to control the many varietions in the are which will tend to change the rate of vaporization of the sample. The probability of expiting the vaporized stom will then change with time. In order to secount for these varietions the internal standard should have the following charecteristics:

1. The internal standard should have an expitation voltage similar to that of the analysis element.

The internal etenderd and enalysis element should have nearly the same rate of vaporisation; their boiling points chould be similar.

3. The internal standard line should be in the came spectral region es the line of the element sought.

4. The internal standard should be present in such a concentration that its line density is approximately the mean value of the density of the element cought in this concentration range.

5. The internal standard should be homogeneously mixed with the sample.

There have been a number of lines suggested for use as an intermal stendard for the determination of mino. Hose, Owens, and Reinhordt (16) in their analysis of organic materials, used molybdenum and biasuth. Rogers (31) suggested the use of tellurium es an intermal standard in the analysis of plant sch. O'Connor (28) in the analysis of mixed fertilizers suggested the use of beryllium es intermal standard. Yansolow and Laurence (53) in the analysis of plant sch used cedmium es an intermal standard. Cedmium was chosen for use se the intermal standard in this analysis of sifelite for mino.

It was desirable to select an internal standard element which could be used with both the mine ins et 213%,6 Angstroms and et 33%,50 Angstroms, and etill possess as many of the previously mentioned characteristics os possible. In practice, no element fulfills all of them, however, in this case, cedaium meets the majority of the requirements for both lines. Both commune and mine have similar excitation voltages, being 6.96 and 9.36 volts, respectively. The two elements have nearly the same boiling points, codmium 767° C. and sine 907° C. Codmium has spectral lines mear the 2136.6 and 3345.0 Angetrom mine lines, located at 214.6 and 3261.1 Angetrom units. The remaining two requirements are easily met in the establishment of experimental conditions. In the seas of analysis using the sine line at 2136.6 Angetroms, the internal standard is added in liquid form to each ash sample; and when the line at 3345.0 Angetroms is used, thoroughly mixed liquid samples are employed.

SPECTROGRAPHIC ANALYSIS OF ALFALFA USING THE ZING LINE AT 2138.6 ANGSTROMS

Preparation of the Standarde

Since extrensous elements are known to effect relative line intensities (20), the standards should have as nearly as possible the same composition as the samples. When using the sine line at 213% 6 Angstroms it is possible to use the plant she directly, and it was found necessary to prepare a synthetic sch mixture similar in composition to the plant sch, but completely free of zino. This synthetic sch mixture, or bess powder, in composed of 5.0 g of potensium dihydrogan phosphate, 16.7 g of potensium cerbonate, 19.6 g of calcium cerbonate, and 3.22 g of magnesium carles. These chemicals were combined, thoroughly mixed, and placed in a maffine at 550 to 475° C. overmight to convert ell compounds to the orides. The resulting dry powder was similar in composition to the plant ssh.

A solution of 0.33 percent odol_2.2d H_2O in hydrochloric soid (1:1) was used as the internal standard. The standard sine solution contained one mg of zine per milliliter. A series of standards were made by edding verying emounts of the standard zine solution with water, and a constant amount of the internal standard, so shown in Table 2.

Table 2. Dilutions used for making a saries of spectrographic standards for use with the zinc line at 2138.6 %.

Standard :	Int. Std. s solution s ml s	Zine soln.	Water ml	: Amt. sine :on electrode : ppm
1	5	0.2	4.8	2
2	5	0.5	4.5	- 5
3	5	1.0	4.0	10
l _e	5	2.0	3.0	20
5	5	3.0	2.0	30

In order to form the working curve about in Fig. 2, an appropriate amount of the bess powder was weighed on to each electrods and 0,1 ml of the spectrographic standard was added. The slectrodes were then dried in an sir owen at 100° C. for several hours. All chemicals used in these analyses were checked spectrographically to show that sine was not present as an impurity.




FIG. 2. WORKING CURVE FOR ZINC 2138 LINE.

Determination of Exposure

In working with mixed fortilizers, C'Gomnor (26) used a logarithmic sector which reduced exposure by 75 percent and found a two end one helf minute exposure under the modified conditions which were employed. This was accomplished by making a moving plate spectrum of the standard containing the highest concentration of mine. Examination of the plate showed the sample to be setiefactorily volatilized at the end of two samutes.

It was found that this exposure time produced excessive background on the photographic plate. To correct this comdition, the rotating sector was used. This permitted the appearum of the sample to be taken during the complete excitation period, however, it reduced the total exposure by an amount proportional to the sector opening. The intensity of the mino line was decreased appreciably when the sector was more than 1/8 slosed. If the number of interruptions for each exposure exceeds 50, Brode (6) has reported that the intermittency effect is negligible. In the analyses reported here the number of interruptions greatly exceeds the minimum, 50.

Preparation of Electrodes

Spectrographic graphite electrodes purchased from the

Netional Cerbon Company were used in these analyses. They were prepared for use by outting the 5/16 inch earbona into 7/8 inch lengths. The anode wee prepared by drilling e well in one end of the electrode, nine to ten mm in depth with wells one to one end one helf nm thick. The cethode was shaped with e shaped with e shaped with e shaped with severy point einlist to e pencil.

The enode wes prepared for the easple by filling the well with eolution of carbon tetrachlorids saturated with carnaube war. Following this the slactrodes were dried in an air oven for 15 minutes at a temperature of 100° C.

Spectrographic Procedure

Two g of dry plant metarial were eshed in e porcelain orusible et e tempereture of 4,50 to 4,75°C. The percent esh was noted end 30 mg samples of the esh weighed into esh else-trode well. Following thie, 0,1 ml of internal standard solution, containing e concentration of cadmium equivalent to that in the spectrographic standards, wee placed on the samples and the electrodes were dried in an eir oven.

Eastman type 103-0 ultraviolet sensitive plates were calcoted so the most cansitive plates evaluable. The camples were croed with e 4.c. potential of 150 volts and a current of 12,5 amperes for a period of two minutes with the sector 7/6 open. The clit width was set at 50 m.q., A series of standards were run on seeh plate.

After exposure the plates were washed for one minute in

ethylens chloride and ellowed to dry before further development. Following this the plates were developed for three ainutes at a temperature of 66° C. in Restman D-19 developer, then fixed and dried. The line intensities were determined with the eid of an A.R.L.-Distort densitonster. A elight background correction we necessary. The results were reported as parte per million on the basis of the dry plant material.

Since it is more convenient to work with solutions, experiments were conducted to determine the possibility of discolving a known weight of eah in a hydrochloric soid solution, An effort was made to dissolve both 60 and 120 mg of plant sh in one milliliter of hydrochloric soid and an eliquot of the resulting solution was to be used for analysis. There was a large residue of insoluble material and the mino lines obtained were too weak to be used for enalysis and others were completely absent; therefore, these experiments were shendomed.

Precision of Analysic Using the Zinc Line at 2138.6 Angstroms

In order to select the better of two methods of snelysis, it is essential to determine the precision and ecoursey of each. The precision of this method wes determined by ceveral enalyses on the same sample. Averages were obtained and the devictions and probable errore were calculated. Table 3 precents data which indicate the precision of the method in the enalyses of a sample of commercially dehydrated elfelfs. The

Table 3. Analyses of commercially dehydrated elfelfs to show precision of the spectrographic method using the line at 2136.6 %.

oa	: Zn	: 2n/	ca	: DDM	1	D 1	D ²
0.135	0.111	0.8	2	15.4	2	22.1	488.4
0.085	0.146	1.7	2	49.3	1	11.8	139.2
0.098	0.180	1.8	4	61.0	2	23.5	552.2
0.161	0.174	1.1	8	24.0	1	13.5	182.2
0.110	0.199	1.8	1	50.5	1	13.0	169.0
0.186	0.227	1.2	2	24.5	_ 1	13.0	169.0
Total					22	24.7	1690.0
Averag	;e				3	37.5	
8 8	standard	devisti	.on =	$\sqrt{\frac{\Sigma D^2}{n-1}}$	=	1690	= 18.4
Standa	rd error	z S _X	=	√n	=	2.24	= 8.21
Probab	le error	s S _X	2	s (8	.21)(0.7}	m 5.74
Percen	t standa	rd error		8.21 37.5	= 2	22 per	cent
Percen	t probab	le error		5.7b 37.5	. 1	15.3 3	ercent

probable error was celoulated to be 15.3 percent. This eample contained 35 perts per million of mine when analyzed by the dithinose colorimetric technique (9) and 37.5 when analyzed epectrographically.

> SPECTROGRAPHIC ANALYSIS OF ALFALFA UBING THE ZING LINE AT 3345.0 ANGSTROMS

Salection of the Spectrographic Buffer

Photocletric densitomatry has greetly increased the precision of measurement of spectral line intensities because small
variations in these intensities can be detacted. Sewarel fectors contribute to these variations which effect enalytical data.
Among these is the effect of extransous elements in the erc.
This condition is due at least in part to the transport mechanism of ions scross the erc. Transport phenomena in are sources
may be the result of an equilibrium between thermal diffusion
of material from the region of the electrods and a migration
of ions of the sample due to electrical forces. Langutroth and
MeMags (20) have investigated transport phenomena and reached
the following conclusions:

- Lines of different elements have, in general, different intensity distributions along their lengths.
- The relative distributions depend on ionization potentiels and masses of the elements, and on the ionization potentiels of other stome present in the discharge.


3. When easily ionized stoms are present in the discharge, the distribution of an element relative to that of a more senily ionized element of comparable mose falls off more sharply toward the unloaded electrods than it does when easily ionized stoms are absent.

The purpose of the epestrographic buffer is to minimize workstions in the transport mechanism from epectrum to spectrum. Requisites of an ecceptable buffer are that it does not emit a complicated spectrum of its own, and that it has a low ionimation potential.

Heee, Owens, and Reinhortt (16) have reported on a number of different buffers for use in the enalysis of organic materials for trace inpurities. They investigated the possibilities of lithium tertrate, potessium broadds with lithium tertrate, potessium nitrate with ammonium nitrate, and colium nitrate. They found codium nitrate the most estimateory for stabilizing the ere conditions for the analysis of several matels. In the analysis of boron Smith (36) has reported fevorably on the way of lithium sphorids as a buffer.

Since the amjority of spectrographic work in this laboretory is done using chloride selts, the use of lithium chloride see a buffer was investigated. Further work led to the selection of lithium chloride see a buffer because it esemed to possess several of the desired characteristics.

A typical celibration curve is shown in Fig. 3. The elight curve at the lower concentration occurs because the lowest point fells on the toe of the plate characteristic curve;



the remainder is on the straight line portion of this ourve,

The buffer for the data reported in this paper was prepared by making a five percent solution of reagast grade lithium chlorids using hydrochloric soid (1:1) as the solvent. This solution was diluted with an equal volume of standard mino solution and water to give a final buffer concentration of two and one helf percent.

Preparation of Standards

In the preparation of standards the buffer solution was made up as previously described, but containing in eddition 0.05 percent CdCl2c.28 EgO es an internal standard. The zinc standard is the same se used previously; it contains one ag of zinc per ml. A series of standards was made by edding varying amounts of the standard zinc solution with water to a constant amount of buffer and internal standard, as shown in Table 4.

In order that the standards would have approximately the same composition as the sample of plant sah efter comeaning-tion, 0-1634 g of NeSO, 7 HgO and 1.765 g of Fe SO, NHR, SO, 6HgO were added to each 100 ml of internal standard.

Table 4. Dilutions used for making a series of spectrographic stendards for use with the mine line et 3345.0 A.

Stenderd	Buffer end : Int. Std.		Weter	: Amt. zine :per sxpoeure : ppm
1	5	0.25	4.75	5
2	5	0.5	4.5	10
3	5	0.75	4.25	15
4	5	1.0	4.0	20
5	5	1.5	3.5	30
6	5	2.0	3.0	40
7	5	3.0	2.0	60

Determination of Exposure

In order that the correct amount of zine be observed in the semple or stenders, it is necessary that the sample be completely reported. The rate of vaporization will depend on the material on the electrodes and the temperature of the arc.

By making a moving plate spectrum of a sample of the spectrographic etandard containing the highest amount of sine, it was found that all of the mine was volatilized in approximately 20 seconds. In order to escount for variations in the are the samples were smitted for 30 seconds. Since this sine line fells very neer the region of the eyanogen bands, it is difficult to reduce plate background without asriously effecting line intensities. It is, however, possible, by use of the roteting sector, to reduce background to such a value that no correction is required. The sector was set t 5/16 open and roteted at a speed greatly exceeding to interruptions per exposure for all exposures.

Preparation of Electrodes

Ordinary graphite spectrographic embons without purifisation or pre-orang were found satisfactory for this daternination. These carbons were purchased from the National Carbon Company, and were prapared for use by sutting the 5/16 inch earbons into 7/8 inch lengths. The anodes were shaped to have a some-like cretar about one and one half am in depth. The cathods were shaped similar to the round noce of a bullet, Smith (36) has shown that electrodes shaped in this manner gave good presistion and the ere had lace tendency to wander.

Before plasing solution on the slackrodes, the srater of the anode was filled with an expess of solution of cerbon tetrashloride saturated with sarasube way. They were then dried in an air owen for approximately 15 minutes. After cooling, the electrodes were ready to reserve the sample solutions, Concentration of the Zinc by Means of 8-Hydroxyquinoline

As hes been previously stated, the zinc present in plant material must be chemically concentrated for spectrographic analysis using the line located at 3345.0 Angestroms. Fleck and Ward (12) have shown that 8-bydroxyquinoline will quantitatively precipitate mine from solution between e pH of 4.58 and 13.4. Berg (5) has shown it possible to quantitatively espected mine from other matels, such as magnesium, copper, and cadmium, but for concentration purposes this separation procedure is not measure. Soott and Mitchell (35) have reported a concentration procedure applicable to plant material using this respect. Their technique, with alight modification, was applied to the sitsife samples pravious to spectrographic analysis.

Your grams of dry plant material were sched in a porcelain crucible at a temperature of 4,50 to 4,750 to. The persent can was noted, and the san quantitatively transferred to a scall evaporating dish. The san was moistaned with a scall amount of distilled water and 15 millilitary of hydrochloric sold (1:1) were added. The solutions were placed on a uniformly heated hot plats and allowed to avaporate to half volume. By this time all seld soluble mine had been extracted and the solution was filtered through a material No. 41 filter paper, and the residue thoroughly washed with boiling water. The resulting solution was diluted to 150 all with distilled water. Hibberd (17) and others have reported that the insoluble ash

conteins gine. The recidue from several easilies were samined spectrographically and no gine could be detected; if any were greent the concentration was below the sensitivity of the mathod. In a majority of the sensite the insoluble residue was small.

Ten al of five percent 6-hydroxyquimoline in sectic seid (2 M) were edded, followed by emmonia (1:1) until the solution became an emarald green. This color is due to the formation of e complex of the respent with iron present. At this point the pH should range between 1.8 and 1.9. Fifty al of ammonias scatts (2 N) were then added, resulting in a pH renging from 5.1 to 5.2. The colution was stirred vigorously and est eside overnight, then filtered through a whatman No. Al filter paper and washed with cold water. After drying, the precipitate was sashed with the paper in a porcelain crueible at 450° C. in an electric suffic.

Spectrographic Procedure

The esh obtained from the 8-hydroxyquincline concentration wes trensferred to a small glass viel and discolved in a minimum of hydrocloric coid (1:1). The solution wes then evaporated to drymass and taken up in two ml of buffer solution containing the internal standard. The solution was thoroughly mixed, and, with a cerological pipet, a 0,10 ml sliquot of the unknown or standard solution was placed on each of the two prepared electrodes. The electrodes with the solutions were placed in en eir owen et 100° C. for sewerel hours, preferebly overnight. A duplicate set of electrodes was needed because of the double exposure used. A series of stendards was run on each plate.

The samples were arosd using a d.e. potential of 120 volts and a current of eight amperes for a period of 30 esconds with the sector 5/16 open. The slit was set at 45 mu.

After exposure the plete were developed four and one helf minute at 66° C. in Mastman X-rey developer diluted two to one. They were then fixed, dried, end the line intensities determined with the use of en A.R.L.-Dietert densitometer.

Raskman 33 blates were used throughout the procedure.

The results were expressed in parts per million of zine, on the dry weight basis.

Precision of Analysis Using the Zino Line et 3345.0 Angstroms

The precision of enalysis using this line was determined for two samples differing widely in consentration. Table 5 presents date used to calculate the precision of analysis of a sample from Morton containing 23.9 ppm of mino. The probable error was found to be 2.12 percent, which is lower than the probable error in the enalysis of a sample from Burlington containing 52.1 ppm. Table 6 presents the data obtained from the Burlington sample in which the probable error was 3.36 percent.

Since the precision of this method is considerably better

Table 5. Analyses of elfelfe from Norton to show precision of spectrographic method using the line at 33k5.0 %.

Cd	: Zn	: 04/zn	1 ppm	1 D	1 D2
9.0	73.8	.122	19.5	4.4	19.36
9.5	76.0	.125	20.5	3.4	11.56
10.0	69.3	.145	27.0	3.1	9.61
8.8	59.8	.147	27.5	3.6	12.96
9.5	71.0	*134	25.0	1.1	1.21
9.3	66.8	.139	25.5	1.6	2.56
9.8	70.3	.139	25.5	1.6	2.56
10.8	75.0	•143	26.2	2,3	5.29
11.8	75.0	•156	28.3	low lo	19.36
10.3	82.5	.124	20.5	3.4	11.56
9.8	75.3	.129	22,2	1.7	2.89
9.0	72.5	.124	20.5	3.4	11.56
8.0	64.0	.125	20.5	3.4	11.56
10.0	70.3	.142	26.0	2.1	4.42
otel			334.7		126.45
verage			23.9		
- st	enderd de	vistion e	$\frac{\Sigma D^2}{n-1}$ =	126.45	• 9.73 • 3.1
		S _x = S	= 3.12 114	= 3.1 3.7	2 = .832
		S _x . 2	a (.83	2)(0.7)	
ercent	standard	error s	23.9	3.46 per	pent
ercent	probable	error =	-582 -	2.42 per	nant

Table 6. Analyses of alfalfs from Burlington to show precision of spectrographic method using the line at 3345.0 ^*

ca	: Zn :	cd/zn	t ppn	i D	D ²
11.0	51.6	.216	46.3	5.8	33.64
10.3	43.5	.230	51.3	0.8	0.64
12.2	49.3	•250	57.5	5.4	29.16
11.2	45.5	.246	57.0	4.9	24.01
12.4	46.5	.267	61.3	9.2	84.64
11.5	55.5	.210	45.0	7.1	50.41
10.0	46.5	.215	46.0	6.1	37.21
Total			364.4		259.71
Avoreg	0		52.1		
Standard	deviation	$= \sqrt{\frac{\mathbf{z} \mathbf{p}^2}{\mathbf{n} = 1}}$	a 25	2.71 =	6.56
Standard	error	s 8 _Z :	<u>S</u> =	6.56	2.5
Probable	error	* Sx. 1	2 =	(2.5)(0.7)	= 1.75
Percent	standard e	Tror =	2.25 =	4.6 percen	t
Percent	probable e	rror =	1.75 =	3.36 perce	nt

than that obtained using the 213% Angstrom line without concentration, it was decided to use the preliminary chamical concentration of the sine followed by analysis using the line located at 33%50 Angstroms.

COMPARISON OF SPECTROGRAPHIC ANALYSIS USING THE 3345.0 ANGSTROM LINE AND DITHIZONE CHEMICAL METHOD

Before epectrographic procedure can be socapted with any degree of confidence, it must undergo a favorable comparison with a well-known chamical procedure. The method used for comparison was identical to the widely used dithizone colorimetric procedure of Cowling and Miller (9). A two and ons half g sample of dry plant material was ashed and the sino extracted in the same manner as for the 8-hydroxyquinoline concentration. The filtrate from the hydrochloric acid extraction was collected in a 100 ml volumetric flask, one drop of methyl red added and neutralized with normal ammonium hydroxide. Four al of normal hydrochloric soid were added and the contente made to volume. A 20 ml sliquot of the sample was pipeted into a 125 ml separatory funnel. The zinc end other slemente, such as copper, lead, and cobalt form a complex with dithizone in carbon tetrachloride end are sxtrected at pH 8.5 to 9.0. The mine was esperated from the copper and excess regent by extraction into 0,02 H hydrochloric ecid. The pH was edjusted to between 8.5 and 9.0 by means of an ammoniaammonium citrate buffer end the zino again extracted with dithizone in the presence of carbamete to prevent interference

by other elements, A fire al sliquot of the extract was placed in a photoelectric colorinater tube (an Evelyn Photoelectric Colorinater manufactured by the Rubican Instrument. Company of Philadelphia) and diluted with 20 al of pure carbon tetrachloride and thoroughly mixed. The percent transmission was determined using a 520 m. filter, and the concentration of sine was determined by comperison with the curve shown in Pin. 4.

A series of nine sifelfs samples were enelysed by this method and compared with spectrographic analysis using the mino line at 3345.0 Angetrons. The results are tabulated in Tablo 7. Examination of the data abous a maximum deviation of 21.2 percent, the everage deviation being 5.5 ppm. The spectrographic analysis results everage approximately 13.6 percent below the colorimetric procedure.

RESULTS OF THE ALPALPA SURVEY

The semples used for the currey were obtained from several localities within the atote. These areas were chosen in such a manner as to represent several of the different soil types found in Manner. All samples were secured at approximately the same stage of growth, that of about one-tenth bloom. This method of sampling would tend to eliminate differences due to varietions in mine content caused by collecting samples of different physiological stages of growth. Fields were eachled by obtaining small amounts of




Table 7. Comparison of spectrographic and dithizons mathods of analysis of elfalfa for sine using the line at 3365.0 M.

Sample :	Dithisone ppm	: Spectrographic ppm	: Deviation :	Percent
Norton	33.3	26.3	-7.0	-21.2
Larned	35.1	28.8	-6.3	-17.9
Hiawatha	35.2	28.8	-6.4	-18.3
Kingman	35.4	28.7	-6.7	-18.9
Meade	38.7	34.0	-4.7	-12.3
Manhettan	39.2	36.8	-2.4	- 6.1
Wakefield	41.7	38.3	-2.4	- 6.0
Burlington	62.0	52.5	-10.5	-16.9
Columbus	68.0	65.0	-3.0	- 4.5
Averege			-5.5	-13.6

elfalfe from several places within the field end than dividing the sample in the usual manner.

A series of eamples of elfelfe being grown on fertilizer plots in two different places in the state were also obtained. These were secured from plots near Theyer and Columbus in order to show the effects of different soil treatments on the sine content of the plant meterial.

An outline mep of Kenses is shown in Fig. 5, including the locations from which semples were secured. The general classification of the soils in those erose, as well as in the entire state, can be readily obtained by reference to a map of Kanses prepared by the Soil Conservation Service (13).

The date in Table 8 represent average enalysic of elfelfe grown on untreated plots in the locations given. Four of the emplee in the eastern region of the etate show the high-east sinc content exhibited in the survey. The emplee in the rest central area show elightly lower mine content, everaging approximately 35 ppm. In general, the mine content decreased ceroes the cateta, being higher in the cast and lower in the west. It is of interest to note that the four extreme eastern eamples which show the highest sinc content have the lowest each content. The esh content, which is indicative of the total mineral content, is lower in the sestern regions. This trend may be partially expected, however, on the basis of reinfell dete end the length of time the land has been farmed. Zinc has been shown by Stokes and Cumnings (40) to be held in the soil largely in a non-water calcula form. The




FIG.5. KANSAS MAP SHOWING WHERE ALFALFA SAMPLES WERE OBTAINED.

Zine and ssh content, of alfalfa taken from untrested plota" in Kansas. Teble 8.

Locality	b		: Ash :	Zino	1 Locality		Ash :	Zino	
Columbus	-	a	7.35	65.0	Abilena	(11)	10.94	33.9	
Thayer	-	5	7.79	28.7	Sedgwlok	(12)	10.87	25.1	
Burlington	-	77)	7.93	52.5	Seline	(13)	10.54	33.7	
Lyndon	-	2	9.44	48.4	Belleville	(77)	8.97	26.3	
Topeka	~	9	7.87	88.8	Kingman	(12)	9.92	28.7	
Metawaka	~	2	9 = 144	29 . ls	Klowe	(10)	10,00	23.9	
Hierratha	-	8	10.26	28.8	Lerned	(11)	11.25	28.8	
Manhatten	_	6	10.90	36.8	Hays	(18)	12.67	31.2	
Wetteffeld	0	(10)	11.45	38.3	Worton	(13)	11.43	26.3	
					Menda	(20)	12.18	34.0	

" Figures are reported on a dry weight basis.

Number following locality corresponds to those on Fig. 5. *

everage reinfall in the Columbus eree has everaged 41.8 inches ennually, eccording to records of the weether bureau, while near Salina the everage has been 27.3 inches. This decreases correspondingly further west.

The date precented in Table 9 indicate the effect of different fartilizer treatments on the quantity of sine found in plant material. The plote on which the fartilizer treatments were carried out ere located comparatively close tomests were carried out ere located comparatively close to gether in the couth eastern corner of the etate. The untreated sample from Theyer was one of the exceptions to the comparatively high mine content of the emples in this region.

The date in Table 9 indicated that epplication of fertilizer to samples grown at Columbus in nearly every cose ceuced e decreece in the esh content. The mine content elso was decreeced in all except two cases. Application of line, manure, and superphosphate in one of the two cases resulted in a elight increase of mine. Each of the fertilizers applied alone, however, caused a decreece in mine. Line and superphosphate applied together in one case out of four caused an increase, the remainder showing lower mine content.

Results of an opposite nature were obtained from applicetion of the seme fortilisers to plots at Theyer. In all except one case the ask content incressed, and only two emples showed a decrease in mine. Either line or menure epplied separetely caused large increases in mine, while the two together show a comparatively small increase. Line in conjunction with manure and rock phosphate showed an increase

Zinc content in alfalfa taken from treeted plots at Thayer and Columbus Teble 9.

		-	T. Same	Chayer		Anna A			-	40000	Columb	ne	1	200
Treatment"; L: 1 No. 1 N	tons	tons	30:	R :	1b.: E	no:	Ash :	tons	ton:	Ib.:	ton:	Ib.: PF	No:	Ash
Mone					28	28.7	7.79					65.0		7.35
×		60			55	4.65	7.60							
ы	8				99	4.89	8.36	1.5				47.8	00	8.01
L. M.	8	to			36	30.08	8.57	1.5	60			36.2	20	7.58
L. M. S.	05	60	150		8	23.5	0°6	1.5	100	120		36.h	4	7.22
								1.05	80	120		69.5	5	6.88
L. M. R.	8	100		1/2	35	39.4	8.73							
L. S.	63		150		36	30.4	8.54	1.5		120		67.5	5	6.75
					26	56.6	8.73	1.5		120		32.5	10	6.02
								1.5		120		27.0h	4	6.62
								1.5		120		33.9	6.	6.53
Le. R.								1.5			1/2	49.2	5/3	16.9
L. 2xS appl.Blen.	~		300		25	50.0	8.77							
L. S. K.	R		150	8	20 34	34.8	8.14	3.05		120	-	16 57	57.2	6,93

³ M. d. mentre; I. M. ground Inneptive; S. d. S. d. veryphoshette; R. M. ground rock propients and K. i. amarket of potent by Coronal Inneptive; S. Tas figures states to quantities per exes and see and K. i. amarkete of potent by Corona (1997). The figures states to quantities per exes and see 20% spoils for house and corona of the corona of the

of approximately 10 ppm zine. Line end double applications of 20 percent superphosphate applied biannially also show e considerable increase in zine.

Lett (21) has shown the availability of nine in soile dependent on pH. At a pH below 6 zinc eesms more resdily evailable and above pH 6 much larger concentrations of sinc do not show toxic affacts. A partial explanation of the results shown in Table 9 may lie in different soil types with respect to pH and total sinc available to the plant. It is also possible that various fertilizers cause fixation of sinc in such a mennar that it is no longer evailable to the plant.

In order to show the effect of the steps of growth on the sine content of sirsife, eachies were taken at Manhattan avery seven days from the time the sirsife first showed spring growth until the time of cutting. The date obtained, which are presented in Table 10, indicated that apparently the sine content decreases slightly during growth. As the plant metures the total mineral content shows an irregular increase, eithough the sine does not seem to decrease in the same ratio,

Table 10. Zinc content' of Manhattan grown alfalfa at seven day intervals up to time of cutting.

Time days	1 1	Height inches	1 1	Ash percent	t t	Zine ppm
7		5		9.73		47.5
14		10		10.89		26.3
21		14		10.52		41.0
28		17		10.86		38.0
35		21		10.15		38.7
42		24		9.38		34+3

^{*} All enelyses reported on dry weight basis.

A spectrographic procedure of good practision for the determination of sinc in plant sah has been developed. The procedure made use of 8-hydroxyquinolins to concentrate the sine and lithium chlorids as a buffer to suppress veristions due to differences in composition and to stebilize the d.c. arc. Conduium was used as the internal standard.

The precision of this method showed a probable error of least ham three percent while the snalysis of alfelfs using the mine time at 213%.6 Angetroms showed a probable error of greater than 15 percent. The spectrographic method using the mine line at 3345.0 Angetroms gave values which compared metidicatorily with the dithizons colorimetric procedure, the average deviation being 13.6 percent below the chamically determined value.

This method was applied successfully to elfelfe plant material, and a survey of the mine content of elfelfe teken from eaverel ereas in Mansac was conducted. The data do not show any area exceptionally low in mine and since the mine requirement of elfelfe has not been established no conclusions regarding a possible mine deficiency in Mansac grown elfelfa could be drawn. Since the effect of fertilization varied with the two experimental plots, there was apparently no correlation between the mine uptake of the plant and the type of fertilization. Line, menure, and superphosphate esperately and in combination appear to cause increased uptake of mine in

some cases. Analyses of alfalfa at various stages of naturity showed a gradual decline in the mine as correlated with an irragular increase of total mineral content.

ACTINOWLEDGRAWATS

The writer wishes to thank Dr. W. G. Schrenk for his sid in the selection of this probles, his liberal donation of time and his helpful suggestions and supervision during this investigation. Thanks are also due to the Depertment of Agronomy of Emness State College and to C. G. Grandfield and Harold Hackgrott of the United States Department of Agriculture for collecting the samples that were used,

LITERATURE CITED

- Alben, A. G. and H. M. Boggs Zinc content of soils in relation to pecen rosatts. Soil Sci. Al: 329-332. 1936.
- (2) Allison, R. V., J. R. Weller and B. E. Robertson. Role of special slamsats in plant development upon the peat and much soils of the averglades. Pla. Agr. Expt. Sta., Ann. Rapt. 114-115, 1935.
- (3) Bernette, R. M., J. P. Camp, J. D. Warner and O. E. Cell. The use of sine suitate under corn and other field crops. Fig. Agr. Expt. Ste. Bul. 292, 49 p. 1936.
- (4) Beeson, K. C. The cocurrence of mineral nutritional diseases of plants and enimels in the United States. Soil Soi. 60: 9-13. 1945.
- (5) Borg, R. Determination and asperation of sinc. Zeitschrift für Analytesche Chemie 77: 171-176. 1927.
- (6) Brode, Wellecs R. Chemical spectroscopy, 2nd ed. Hew York. John Wiley. 677 p. 1943.
- (7) Branchley, Windfred. The assential nature of certain minor elements for plant nutrition. Botanical Rev. 2: 173-179, 1936.
- (8) Camp, A. F. Zino as a mutrient in plant growth. Soil Sci. 60: 157-161. 1941.
- (9) Cowling, Hele and S. J. Miller. Determination of smell amounts of gine in plant meteriel. Indus. and Engin. Chem., Analyt. Ed. 13: 145-149. 1941.
- (10) Fellers, C. R. The effect of inoculation, fertiliner treatment end osrtain minerals on the yield, composition, nodula formation of soybeans. Soil Set. 5: 81-129, 1918.
- (11) Fischer, Hellant and Gretz Leopoldi. Nathwest and bestimming kleiner Zmkmengen mit dithizone. 107: 271-269. 1936.

- (12) Fleck, R. H. and A. M. Ward. The determination of metals by the means of 6-hydroxy-quincline, Analyst 56: 388-394, 1933.
- [13] Fly, C. L. Natural agricultural resource cross of Kanses. Reprint from Report of Kanses State Board of Agriculture. 70 p. Fab. 1946.
- (14) Gerlach, W. Z. and Schweitzer. Foundations and mathods of chemical analysis by the emission spectrum. Adam Hilger Ltd. London. 1929.
- (15) Harter, L. L. and W. T. Zaumeyer.

 A monographic study of bean dissess and methods for their control. U. S. Dept. Agr. Tech. Bul. 868, 67 p. 1944.
- (16) Hess, T. M., J. S. Cwens and L. G. Reinhordt. Analysis of organic materials for treess of metallic impurities. Indus. and Engin. Chem., Analyt. Ed. 11: 040-048. 1939.
- (17) Hibberd, P. L. Micro methods for determination of zine. Indus. and Engine Chems, Analyt. Ed. 6: 423-425. 1934.
- (18) Holland, E. B. and W. S. Ritchie. Report on the determination of zine in foods. Jour. Assoc. Official Arx. Chem. 22: 333-338. 1939.
- [19] Jevillier, M. Le zinc chaz les plantes recharches sur su presence it son role. Annals Institut Pasteur. 22: 720-727. 1908.
- (20) Langstroth, G. C. and D. R. McRee. Transport of metarial in sources for spectroscopic analysis. Canad. Jour. Nes. 164: 61-74. 1938.
- (21) Lott, W. L. The relation of hydrogen ion concentration to the availability of sine in soil. Soil Sci. Soc. Amer. Proc. 3: 116-119. 1938.
- (22) Lyman, C. and L. A. Dean. Zino deficiency of pineepples in relation to soil and plant composition. Soil Soi. 54: 315-324. 1942.
- (23) Mase, P. Recherches de physiologis regetels. Influences respectives des elements de la mineral sur le developpement du mais. Annales De Instit. Pesteur 28: 21-57. 1914.

- (24) Moze, P.
 Recherche d'une solution purement mineral cepable
 d'essurer l'avolution complete des murulies. Annelee
 de Instit. Pasteur. 33: 139-144. 1919.
- (25) Merrit, L. L. Determination of small amounts of gine by measurement of fluorescent turbidities. Indus. and Engin. Chem., Analyt. Ed. 11: 758-760. 1984.
- (26) McHargue, J. S. The effect of manganese, copper, zine, boron end ereenic on the growth of cets. Amer. Soc. Agron. Jour. 221 727-759. 1930.
- (27) Millikan, C. P. Symptoms of sino deficiency in whest end flax. J. Austrelian Inst. Agr. Sol. 8: 33-35. 1942.
- (28) O'Connor, R. T.
 Spectrochemical enalysis of trees elements in fertilizers
 (zine). Indus. and Engin. Chem., Analyt. Ed. 3: 597600, 1941s
- (29) Parker, E. R. Experiments on the trestment of mottle lesf of citrus trees. IV. Amer. Hort Soc. Proc. 35: 217-226. 1938.
- (30) Reed, J. F. end R. W. Cummings. Determination of sinc in plant materials using the dropping mercury electrode. Indus. end Engin. Chem., Analyt. Ed. 12: 489-492, 1940.
- (31) Rogers, L. H. Spectrographic microdetermination of zine. Indus. and Engin. Chem., Aprlyt. Ed. 7: 421-422, 1935.
- (32) Rogers, L. H. and O. E. Gell. Microdetermination of zine. Comparison of spectrographic and chemical methods. Indus. and Engin. Chem., Analyt. Ed. 9: 42-44. 1937.
- (33) Robinson, W. O. and O. Edgington. Minor elements in plants, and some accumulator plants. Soil Soi. 50: 15-28. 1953.
- (34) Sandell, E. B. The determination of copper, mine, and leed in silicate rocks. Indus. and Engin. Chem., Analyt. Ed. 9: 465-469, 1937.

- (35) Scott, R. G. and R. L. Hitchell. Onesentration asthod in spectrographic enclysis T. Recovery of cobalt, nickel, molybdenum, copper, and zinc from plant materials and soil extracts by 8hydroxyculnoline. Four. Soc. Chem. Ind., 62: 4-8, 1943.
- (36) Smith, F. M. Spectrographic determination of boron in plant tissue; survey of the boron content of Kansas grown elfels and wheat. Unpublished Master's Thesie, Kane. Stats Coll. Agr. and Appl. 501. 50 p. 1945.
- (37) Saith, F. M., W. C. Schrank and H. H. King. Survey of the boron content of Kansas grown elfalfe. Kansas Acad. Soi. Trans. 50: 342-348. 1948.
- (38) Sommer, A. L. and C. B. Lipman. Evidence on the indispenseble nature of zinc and boron for higher green plante. Plant Physiol. 1: 231-249. 1926.
- (39) Sommer, A. L. Further evidence on the essential nature of zinc for the growth of higher green plants. Flant Physiol. 3: 217-221, 1928.
- (40) Stokes, E. V. and R. W. Cummings.
 The influence of mino on the productivity of certain
 New York peet soils. Soil Sei. Soc. Amer. Proc. 6:
 207-214: 1941.
 - (41) Stiles, Welter. Trace elements in plants and snimels. New York. Macmillan. 178 p. 1946.
- (42) Thorne, D. W., W. D. Lews and A. Wallace. Zinc relationships of some Uteh soile. Soil Soi. 54: 653-666. 1942.
- (43) Veneslow, A. P. and B. M. Leurence. Spectrographic aloredetermination of sinc. Indus. and Engin. Chem., Analyt. Ed. 8: 240-242. 1936.
- (44) White, E. E. end M. H. Neustedt. Benzoin ee s fluorecent qualitative reagent for zino. Indus and Ragin. Chem., Amslyt. Ed. 15: 599-601. 1943.
- (45) Young, R. S. Cartein rarer elemente in soils and fertilizers, and their role in plant growth. New York (Cornell) Agr. Expt. Ste. Memoir. 174. 68 p. 1935.