

CALCULATION OF ENERGY AND ANGULAR DISTRIBUTION OF  
WALL SINGLE SCATTERED GAMMA RADIATION FROM A  
SEMI-INFINITE ISOTROPIC PLANE SOURCE

by *1264*

JAMES MILTON ROYER

B. S., Kansas State University, 1965

---

A MASTER'S THESIS

submitted in partial fulfillment of the  
requirements for the degree

MASTER OF SCIENCE

Department of Nuclear Engineering

KANSAS STATE UNIVERSITY

Manhattan, Kansas

1970

Approved by

*Richard E. Fawcett*  
Major Professor

LD  
2668  
T4  
1970  
R68

TABLE OF CONTENTS

1.0	INTRODUCTION.....	1
2.0	THEORY.....	3
3.0	CALCULATIONS.....	9
4.0	RESULTS.....	25
5.0	DISCUSSION OF RESULTS.....	72
6.0	ACKNOWLEDGEMENT.....	78
7.0	REFERENCES.....	79
8.0	APPENDICES.....	80
	APPENDIX A: DESCRIPTION OF EXPERIMENTAL WORK.....	81
	APPENDIX B: INFINITE SOURCE APPROXIMATION.....	107
	APPENDIX C: SAMPLE CALCULATION.....	110
	APPENDIX D: COMPUTER PROGRAM.....	118

## LIST OF FIGURES

Figure	Page
2-1	Isotropic view of a scattering event.....4
2-2	Enlargement of the center section of the wall showing a scattering event.....5
2-3	Scattering event shown in the scattering plane.....6
3-1	Geometry for thin slab calculations.....10
3-2	Variation of differential flux with number of thin slabs...14
3-3	Differential flux as a function of distance of unit point $^{60}\text{Co}$ source from verticle centerline of test slab, detector location $\xi = 0^\circ$ , $\eta = 0^\circ$ .....17
3-4	Detector position parameters.....18
4-1	Comparison of calculated single scattered flux with measured flux for a point source.....16
4-2	Comparison of calculated single scattered flux with measured flux for a point source.....27
4-3	Comparison of calculated single scattered flux with measured flux for a point source.....28
4-4	Approximate source areas used in calculations.....30
4-5	Wall single scattered Exposure Rate angular distribution from a semi-infinite plane source at a point 3 ft above grade.....31
5-1	Comparison of calculated single scattered flux with measured flux, Area 2, $\cos \theta_d = 0.2$ , $\phi_d = 0^\circ$ .....73
5-2	Comparison of calculated single scattered flux with measured flux, Area 2, $\cos \theta_d = 0.4$ , $\phi_d = 0^\circ$ .....74
5-3	Comparison between redistributed single scattered flux and measured flux, Area 2, $\cos \theta_d = 0.2$ , $\phi_d = 0^\circ$ .....76
5-4	Comparison between redistributed single scattered flux and measured flux, Area 2, $\cos \theta_d = 0.2$ , $\phi_d = 0^\circ$ .....77

Figure	Page
A-1 View of test facility.....	84
A-2 Test panel structure.....	85
A-3 Wooden forms for concrete test panel.....	86
A-4 Source tubing Area 1.....	87
A-5 Source tubing Area 2.....	88
A-6 Source tubing Area 3.....	89
A-7 Grading plan.....	90
A-8 Measurement of test panel mass thickness.....	92
A-9 Machine drawing of collimator system.....	94
A-10 View of collimator.....	97
A-11 Configuration for collimator positioning and alignment....	102
A-12 Winch and pulley locations for collimator leveling system..	104
A-13 Comparison of background spectrum with total spectrum....	106
C-1 Initial reference frame used in computer code.....	111
C-2 Secondary reference frame used in single scattering computer code.....	113
C-3 Triangle defined in the scattering plane.....	114

## LIST OF TABLES

Table	Page
3-1 Exposure rate conversion factors for energy bins.....	13
3-2 Variation of energy spectrum and total exposure rate with cahnge in $\Delta v$ 's of the source plane for a 1 ft wide annulus at the given r.....	19
3-3 Variation of energy spectrum and total exposure rate with change in $\Delta v$ 's of the source plane for a 1 ft wide annulus at the given r.....	20
3-4 Variation of energy spectrum and total exposure rate with change in $\Delta v$ 's of the source plane for a 10 ft wide annulus at the given r.....	21
3-5 Variation of energy spectrum and total exposure rate with change in $\Delta r$ 's of the source plane for a 10 ft wide annulus at the given r.....	22
3-6 Variation of energy spectrum and total exposure rate with change in $\Delta r$ 's of the source plane for a 10 ft wide annulus at the given r.....	23
3-7 Variation of energy spectrum and total exposure rate with change in $\Delta r$ 's of the source plane for a 100 ft wide annulus at the given r.....	24
4-1 Calculated single scattered exposure rates for point sources.....	25
4-2 - 4-41 Energy angular distribution of single scattered photons for a wall barrier exposed to a plane isotropic Co-60 source for $\cos \theta_d = \pm 0.1, \pm 0.2,$ $\pm 0.4, +0.7, -0.48$ at $\phi_d = 0^\circ, 10^\circ, 20^\circ, 35^\circ,$ and $45^\circ$ .....	32-31
C-1 Values of the mass attenuation coefficient $\mu/\rho$ , less Rayleigh (coherent) scattering and the photonuclear effect, for air and concrete.	