

A STUDY OF A CAFETERIA SYSTEM
USING DIGITAL SIMULATION

by 1264

VED PARKASH AGGARWAL

B.E. (Mechanical Engineering),
Punjab University, Punjab, India, 1963

A MASTER'S THESIS

submitted in partial fulfillment of the
requirements for the degree

MASTER OF SCIENCE


Department of Industrial Engineering

KANSAS STATE UNIVERSITY

Manhattan, Kansas

1970

Approved by:


Major Professor

LD
2668
T4
1970
A37

TABLE OF CONTENTS

| | PAGE |
|---------------------------------------------------------------------------------|------|
| ACKNOWLEDGEMENT | ii |
| LIST OF TABLES | iii |
| LIST OF FIGURES | iv |
| CHAPTER 1. INTRODUCTION | 1 |
| 1.1 DESCRIPTION OF THE CAFETERIA SYSTEM | 1 |
| CHAPTER 2. LITERATURE REVIEW | 4 |
| CHAPTER 3. THE PROPOSED PROBLEM | 11 |
| 3.1 PURPOSE OF THE STUDY | 11 |
| 3.2 SYSTEM DESCRIPTION | 13 |
| 3.3 ASSUMPTIONS | 14 |
| 3.4 DATA FOR THE EXPERIMENT | 15 |
| CHAPTER 4. DESIGN OF THE SIMULATION MODEL | 23 |
| 4.1 COMPUTER PROGRAM | 23 |
| 4.2 PROGRAM DESCRIPTION | 26 |
| 4.3 COMPUTER MODEL VALIDATION | 32 |
| CHAPTER 5. THE ANALYSIS OF SIMULATION RESULTS | 37 |
| 5.1 STEADY STATE | 37 |
| 5.2 DETERMINATION OF NUMBER OF CHECKER AND CASHIER STATIONS | 42 |
| 5.3 THE EFFECT OF VARIATION IN SERVICE TIME DISTRIBUTION FOR CHECKOUT OPERATION | 52 |
| 5.4 THE EFFECT OF VARIATION IN ARRIVAL RATE OF CUSTOMERS | 62 |
| CHAPTER 6. SUMMARY AND CONCLUSIONS | 68 |
| REFERENCES | 70 |
| APPENDIX A. PROGRAM BLOCK DIAGRAMS | 72 |
| B. PROGRAM | 78 |
| C. THE TYPICAL OUTPUT | 82 |

ACKNOWLEDGMENTS

The author is deeply indebted to his major advisor, Professor J. J. Smaltz, for his encouragement, guidance and assistance in the preparation of this manuscript.

Grateful appreciation is also expressed to Mrs. Grace Shugart, Head, Department of Institutional Management, for her help in developing this manuscript, and to Dr. L. E. Grosh, Department of Industrial Engineering, for his valuable suggestions.

The author wishes to express his sincere appreciation to his wife, Nina Rani, for her patience, constant encouragement and understanding without which this endeavor could not have been accomplished.

LIST OF TABLES

| TABLE | PAGE |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 1. Mean inter-arrival time for each model. | 20 |
| 2. Comparison of observed data with simulated data using mean service time of each facility. | 33 |
| 3. Effect of number of checker stations on the mean waiting time of the customers, per cent utilization of checkers, and the maximum queue length for model 3. | 44 |
| 4. Effect of number of service station on the per cent of customers waiting more than 0.75 minute. | 45 |
| 5. Effect of number of cashier stations on the mean waiting time of the customers, per cent utilization of cashiers, and the maximum queue length for model 3. | 46 |
| 6. Effect of number of checker-cum-cashiers on the mean waiting time of the customers, per cent utilization, of checker-cum-cashiers, and the maximum queue length for model 1. | 53 |
| 7. Effect of number of checker-cum-cashiers on the mean waiting time of the customers, per cent utilization of checker-cum-cashiers, and the maximum queue length for model 2. | 54 |
| 8. Effect of the number of checker-cum-cashiers on the mean waiting time of the customers, per cent utilization of checker-cum-cashiers, and the maximum queue length for model 4. | 55 |
| 9. Effect of variation in service time of checker-cum-cashier on the mean waiting time of customers, time between departures, and per cent utilization of checker-cum-cashiers. | 63 |
| 10. Effect of variation in mean arrival rate of customers on the mean waiting time of the customers, per cent of customers waiting more than 0.75 minute, time between departures, and per cent utilization of checkout stations. | 66 |

LIST OF FIGURES

| FIGURE | PAGE |
|------------------------------------------------------------------------------------------------|------|
| 1. Schematic diagram of a cafeteria system. | 3 |
| 2. Mean arrival rate of customers during the day. | 18 |
| 3. Cumulative frequency distribution of service time at checker station. | 34 |
| 4. Cumulative frequency distribution of service time at checker-cum-cashier station. | 35 |
| 5. Cumulative frequency distribution of service time at cashier station. | 36 |
| 6. The mean time between departures and per cent utilization of checker-cum-cashier: Model 1. | 38 |
| 7. The mean time between departures and per cent utilization of checker-cum-cashier: Model 2. | 39 |
| 8. The mean time between departures and per cent utilization of checker: Model 3. | 40 |
| 9. The mean time between departures, and per cent utilization of checker-cum-cashier: Model 4. | 41 |
| 10. Distribution of waiting times of customers at checker stations: Model 3. | 47 |
| 11. Design curves for various numbers of checker stations: Model 3. | 48 |
| 12. Design curves for various numbers of cashier stations: Model 3. | 50 |
| 13. Distributions of waiting times of customers at cashier stations: Model 3. | 51 |

| FIGURE | PAGE |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 14. Design curves for various numbers of checker-cum-cashiers: Model 1. | 56 |
| 15. Design curves for various numbers of checker-cum-cashiers: Model 2. | 57 |
| 16. Design curves for various numbers of checker-cum-cashiers: Model 4. | 58 |
| 17. Distributions of waiting times of customers at checking-cum-cashing operation: Model 1. | 59 |
| 18. Distributions of waiting times of customers at checking-cum-cashing operation: Model 2. | 60 |
| 19. Distributions of waiting times of customers at checking-cum-cashing operation: Model 4. | 61 |
| 20. Relationship between mean service time, per cent of the customers waiting more than 0.75 minute, per cent utilization, and mean time between departures. | 64 |
| 21. Relationship between the number of arrivals, per cent of the customers waiting more than 0.75 minute, per cent utilization and mean time between departures. | 67 |
| 22. Block diagram for cafeteria system: Models 1, 2, and 4. | 73 |
| 23. Block diagram for cafeteria system: Model 3. | 75 |